

From: _____

Fax: _____

Email: _____

**Request for QUOTATION from AMERACE
For a Waterproof Voltage Transformer
Fax +1 905 882 8014**

Transformer Technology

All transformers use the same technology, as listed under "Common Specifications" below. In addition, you may choose any of the following options. Please be sure to complete each section.

Power Rating

- 30W 45W 65W 100W 150W
- 200W 250W 300W 400W 500W Other _____W (max.600W)

Primary lead length

- 0,6 meter Other _____ meters (minimum 0,3, maximum ?)

Primary Connectors

- First lead T Connector FAA Style 2 plug FAA Style 9 receptacle None
- Second lead T Connector FAA Style 2 plug FAA Style 9 receptacle None



Secondary lead length

- 1,2 meters Other _____ meters (minimum 0,3, maximum ?)

Secondary Connectors

- FAA Style 7  FAA Style 8  None

Primary Voltage

- 110V 220V 360V 480V 600V 2400V Other _____A
(max.4500V)

Secondary Voltage

- 6,9V 12V 15V 30V 45V 110V 220V Other _____A
(max.600V)

Common Specifications

Construction

Core	Flat laminations (E&I) of high grade grain oriented silicon steel for a long, stable life.
Encapsulant	TPR rubber (also known as TPV, TPE) <ul style="list-style-type: none">• Much higher dielectric strength and lower water absorption than older materials such as epoxy, neoprene, or polychloroprene.• Minimal swelling in the presence of hydrocarbons, unlike neoprene, polychloroprene, etc.
Encapsulation process	Injection molding for maximum consistency of encapsulation, yielding exceptionally low leakage currents. Vacuum drawing prior to injection prevents air pockets inside. A far superior process to compression or transfer molding, or pouring.
Winding	Magnet wire on a plastic bobbin, specifically designed to electrically isolate the primary and secondary windings for maximum safety.
Connector pins and sockets	Tin plated for corrosion resistance
Primary cables	Cable is AWG #8 (8,3 mm ²) Type C TPR for maximum reliability
Secondary cable	Cable is AWG 2/12 (3,3 mm ²)
Material compatibility	Transformer body, cables, and connectors are all molded of TPR for perfect bonding.
Waterproofness	Amerace® transformers are designed and manufactured to operate submerged in water indefinitely.

Electrical

Insulation Level	5000 V RMS
Efficiencies	85% to 95% depending on the power rating
Power Factor	> 0,97 for resistive loads
Frequency	50/60 Hz
Certification	Responsibility of buyer to obtain approval for use from local electrical authority
Testing	All units (100%) are hipotted and the output voltage confirmed

Environmental

Operating Temperature Range	-55°C to +65°C
Contaminant resistance	Suitable for areas contaminated with most oils, aircraft fuels, soil acids and alkalis, and deicing fluids. Resistant to UV exposure and ozone.

Installation Options

All types, including above ground, in concrete or other non-metallic pits, in metal cans, or direct buried.